




L&C

LABELING  
& CODING

# MFLEX™ HUGGER BELT

## PRESSURE-SENSITIVE LABEL APPLICATOR SYSTEM



### Engineered for Modularity and Flexibility

MFlex Hugger Belt is a labeling system that uses hugger belts to move the product to be labeled through the label application section of the machine. This allows for many types of packages to be labeled, especially when other conveyor designs make it difficult to apply the label in the required location on the package.

The MFlex Hugger Belt can be configured with either one or two labeling heads, making it ideal to label either or both sides of the product, as well as having the ability to apply a c-wrap label that spans two sides.

The twin hugger belt product control module is simple to adjust for different package sizes, making changeover quick and efficient.

### FEATURES AND BENEFITS

- Closed-loop electric servo system to ensure maximum synchronization and control
- Singular full color touch-screen HMI provides fast access to any adjustments as well as full diagnostics for maintenance.
- Built on a welded stainless steel frame, using non-corrosive components that feature IP65 protection.
- Modular components for maximum serviceability.
- Tool-free design for easy and fast adjustments.
- Compact high-powered brushless DC conveyor and product handling motors.
- Zero downtime option featuring redundant labeling heads for continuous labeling production.

### COMMON APPLICATIONS






# MFLEX™ HUGGER BELT PRESSURE-SENSITIVE LABELING SYSTEM

## STANDARD PRODUCT SPECIFICATIONS

<b>Label Supply</b>	12" Diameter / 3" Core		<b>Electrical</b>	120V AC @ 6A, 60Hz
<b>Label Size</b>	Min: 1" x 2" Feed	Max: 5" x 10" Feed Max: 5" x 24" Feed*	<b>Conveyor Speed</b>	Variable up to 125ft per minute
<b>Product Size</b>	4" to 12" Wide	2" to 24" Long	<b>Conveyor</b>	Stainless Steel, Aluminum, UHMW
<b>Operation</b>	Closed-loop Electric Servo		<b>IP Rating</b>	IP65 Wet/Damp Environment

\*Maximum c-wrap application label size (Top labeling head only).

## CONFIGURATION



## SYSTEM OPTIONS

- 16" (407mm) OD Label Supply
- Increased Label Width
- Low Label Supply Warning with Auto Shut-Off Feature and Beacon light
- Different Supply Voltage
- Clear Label Sensor Package
- Additional Conveyor Width
- Additional Conveyor Length
- Adjustable Hugger Belt Height
- Adjustable Feet
- Higher Speed

©2022 ProMach Inc. ProMach reserves the right to change or discontinue specifications and designs shown in this brochure without notice or recourse  
EPI\_SpecSheet\_MFlex Hugger Belt\_061523



PHONE  
717-235-8345

TOLL FREE  
800-755-8344

EMAIL  
EPI@ProMachBuilt.com

WEB  
EPILabelers.com

1145 East Wellspring Rd  
New Freedom, PA 17349